# 1 SMD LED Module, 0.7W White 5050 LED(35mmx18mm)

Item Code: LED module-LBY-ZH351F-1CWF



| | |
|---|---|
| FOB Price: | **$1.96/pc** |
| Mini Order: | 200 pcs |
| Average Rating: | lb (kg) |

[Inquire Now](#)

## Overview

**Characteristic:**
- High brightness LED SMD as a lamp-house, having a wide angle view and petty aperture.
- Controlled by the chips with constant current, having constant working current and indiscriminate between the cathode and anode.
- Low voltage, safe and jar less.
- With a settled orifice and 3M gummed paper, very convenient to install.
- Long life time, above 50000hrs.
- Low power consumption, energy conservation and saving electricity.

**Application:**
This LED SMD module is used for solid lighting character, LED signs, LED lighting box, scenery designs, décor, etc.

## Details

| | |
|---|---|
| SMD Package Model | 5050 |
| Color | White |
| Shape | Other |
| Brightness | High |
| LED Number | 1 |
| Material | Plastic |

# Specifications

| Basic parameters | | | |
|---|---|---|---|
| Color | White | LED type | 5050 SMD |
| LED Qty | 1 pcs | Dimension | 35 x 18 x 6mm |
| Module interface | Gray 0.5mm2×75mm RVleads | Interface definition | Gray anode, white cathode |
| Cluster Qty | 20pcs | Module space between | |
| Weight | 15g±5? | Lifespan | MTBF?50000hours |
| Environment parameters | | | |
| Working temperature | -40?~ 65? | | |
| Defend grade | IP65 | | |
| Electronic specifications | | | |
| Working input voltage | D12V±5% | Max power | 0.6W |
| Driving mode | Constant current driving | | |
| Lighting capability | | | |
| Luminous flux | 80lm | | |
| Beam angle | >120° | | |