

110.2" (2.8m) Coated Backlit

Item Code: BS-CB005-110R-GL-1



FOB Price: **\$323/roll**

Mini Order: 40 rolls

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Samples:



sample 1



sample 2

Details

Width	110.2" (2.8m)
Length	54.6Y(50m)
Speci-	250*250 36*36

Specifications

Item	Metric	Test Method
Weight	510±10gsm	DIN53352 BS3424
Breaking Strength	2100/1850N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	300/250N	DIN53356 BS3424
Adhesion	80N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (1010)	
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC or PVDF	
Cd	We can reach: EN71-3	



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com