

110.2" (2.8m) Coated Blockout

Item Code: BS-CF017-110R-GL



FOB Price: \$341/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview



Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.
- . Double side printable.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Specifications

Item			Metric	
Neight	610±10	gsm		DI
Breaking Strength	1850/1350	N/2.0" (5cm)		DI
Tearing Strength	235/220	Ν		DI
Adhesion	80	N/2.0" (5cm)		DI
Width	Up to 11.5' (350cm) (0505)		
FR Certification	We can read	ch:M2,B1,B2,DIN7	75200,NFPA701	
Lacquering	Products ca	n be lacquered wit	th ACRYLIC or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can read	ch:EN71-3		



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com