

110.2" (2.8m) Coated Mesh Fabric

Item Code: BS-M518-110R-TC



FOB Price: **\$204/roll**

Mini Order: 40 rolls

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Product Characteristic:

- . High strength, anti-tensile, anti-tearing.
- . Good ventilating ability, natural lighting.
- . Color expressive.
- . Three-dimensional printing effect available.
- . Anti-typhoon, thus could be put on the roof of the building.
- . Flame retardant, safe.
- . weather resistant, suitable for both indoor and outdoor.
- . Low cost and easy to use.

Product Description:

Smooth, high bonding strength, good and stable ink absorbing, self-cleaning, fast drying up, perfect printing effect, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Digital printing, screen printing for wall murals, building cover & signboard.

Specifications

Item	Metric		Test Method
Weight	270	gsm	DIN53352 BS3424

Breaking Strength	850/1100	N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	200/215	N	DIN53356 BS3424
Adhesion	/	N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (1010)		
FR Certification	M2,B1,B2,DIN75200,NFPA701		
Lacquering	Products can be lacquered with ACRYLIC or PVDF		
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3		



NETSUITE®
ONE SYSTEM. NO LIMITS.



Member
INTERNATIONAL
SIGN ASSOCIATION



Member
Specialty Graphic Imaging Association



ACCREDITED
BUSINESS

Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com