


# 125.9" (3.2m) Coated Blockout

Item Code: BS-CF016-125R-GL



FOB Price: \$338/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

**Inquire Now** 

## **Overview**

#### **Description:**

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.



#### **Characteristic:**

- . Completely light tight.
- . Anti-UV, weather-resistant.
- Mildewproof, antifouling processed surface.
- Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.
- . Double side printable.

### Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

## **Specifications**

Item	Metric	Test Method
Weight	440±10gsm	DIN53352 BS3424
Breaking Strength	1300/1030N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	115/105N	DIN53356 BS3424
Adhesion	80N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (2525)	
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3	























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com