

125.9" (3.2m) Coated Mesh Fabric

Item Code: BS-M112-125R-TC



FOB Price: \$259/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . High strength, anti-tensile, anti-tearing.
- . Good ventilating ability, natural lighting.
- . Color expressive.
- . Three-dimensional printing effect available.
- . Anti-typhoon, thus could be put on the roof of the building.
- . Flame retardant, safe.
- . weather resistant, suitable for both indoor and outdoor.
- . Low cost and easy to use.

Product Description:

Smooth, high bonding strength, goog and stable ink absorbing, self-cleaning, fast drying up, perfect pringting effect, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Digital printing, Screen printing for Wall murals, Building cover & signboard.

Specifications

gsm

Test Method

DIN53352 BS3424

Breaking Strength		850/1000	N/2.0" (5cm)	DIN53354 BS3424	
Tearing Strength		190/200	Ν	DIN53356 BS3424	
Adhesion		/	N/2.0" (5cm)	DIN53357 BS3424	
Width	Width Up to 11.5' (350cm) (0510)				
FR Certification M2		M2,B1,B2,I	M2,B1,B2,DIN75200,NFPA701		
Lacquering Pro		Products ca	Products can be lacquered with ACRYLIC or PVDF		
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%		We can rea	We can reach:EN71-3		



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com