



2-SMD 3528 Water proof module 26x7mm

Item Code: LED module-LBY-3F12T2607-2CWF



FOB Price: **\$0.33/pc**

Mini Order: 200 pcs

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Characteristics:

- . High brightness LED SMD as a lamp-house, has a wide angle view and petty aperture.
- . Controlled by the chips with constant current, having constant working current and indiscriminate between the cathode and anode.
- . Low voltage, safe and jar less.
- . With a settled orifice and 3M gummed paper, very convenient to install.
- . Long life time, above 80000hrs.
- . Low power consumption, energy conservation and saving electricity.

Application:
This LED SMD module is used for solid lighting character, LED signs, LED lighting box, scenery designs, décor, etc.

Sample:



Details

Material	Plastic
LED Number	2
SMD Package Model	3528
Color	White
Shape	Rectangular
Brightness	Low

Specifications

	Basic parameters		
Color	Red, yellow, blue, green, white	LED type	3528 SMD
LED Qty	2PCS	Dimension	1.0" x 0.3" (26 x 7mm)
Module interface	Gray 0.5mm 0.1" x 3.0" (2 x 75mm) RVleads	Interface definition	Gray anode, white cathode
Cluster Qty	20pcs	Module space between	

Weight	0.4oz (10g)±5%	Lifespan	MTBF>50000hours
Environment parameters			
Working temperature	-40°C?60°C		
Defend grade	IP68 completely satisfies the outdoor lighting standard		
Electronic specifications			
Working input voltage	D12V±5%	Max power	0.15 W
Driving mode	Invariable voltage! (Insure every LED working under the invariable voltage)		
Lighting capability			
Luminous flux	0.4floz (12lm)		
Beam angle	160°-180°		



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com