



## **BX-5M3 + HUB LED Display Graphic Controller**

Item Code: LED-VS-BX-5M3-HUB



FOB Price: **???.2 570/??.**

Mini Order: 1 ??.

Average Rating: 1b (kg)

[Inquire Now](#)

---

### **Overview**

---

**Specification:**

**Product name:**BX-5M3 LED graphic controller

**Control point monochrome 128K point:** 3200\*32 2720\*48 2048\*64 1632\*80 1344\*96 1152\*112 1024\*128 3200\*16  
Dual color 64K point: 2048\*32 1360\*48 1024\*64 816\*80 672\*96 576\*112 512\*128 3200\*16

**Storage capacity:** 2MByte

**Adaptation range:** A variety of single / double color LED displays

**Software function:** Cluster management / multi program editing / multi zone display / multi language version

**Program type:** Ordinary programs / shared programs

**Number of programs:** Support 128 programs, each program is divided into 24 areas

**Region type:** Graphic / subtitles / animation / lunar / time / analog dial / positive timing / temperature / temperature

**Border display:** Colorful magic show / advanced border border

**Xuandong background:** Support

**Clock display:** Chinese calendar / analog dial / Chinese / English clock / plus / minus timing (both support multi group display)

**Communication interface:** 100M network port and USB interface

**Display interface:** 1 groups of 50PIN interface

**Sensor support:** Temperature / humidity

**Remote control function:** Program selection / screen lock / brightness adjustment / switch / screen test

**Brightness adjustment:** 16 levels of brightness, support Shidiao light / lightening / light remote control software

**Remote switch:** Support timing automatic switch / software switch / remote control switch

**Working voltage:** 5V (3.5V ~ 6.5V wide operating voltage)

**Maximum power:** Less than 2W

**Ambient temperature:** -40 C ~ 80 C

**Two development:** DLL dynamic library with complete functions

**Software kit:** LedshowTW graphic editing software

**Use manual:** Dual color LED graphic controller user manual

**Display adapter card:** HUB128-T8 HUB256-T12 HUB128-T12 HUB256-T8

**USB transmission distance description:**

BX-5U series using USB1.1 protocol, the speed of 12Mbit/S, the transmission distance of 12 meters;

BX-5M series using USB1.1 protocol, the speed of 12Mbit/S, the transmission distance of 12 meters;

BX-5E series using USB1.2 protocol, the speed of 12Mbit/S, the transmission distance of 6 meters.



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com