

24" Standard Vinyl Cutting Plotter

Item Code: CPM-LD-620H



Overview

CPM-LD-H Series Standard Vinyl Cutter With LCD

With LCD operation-Updated from CPM-LD economical model Up to 28.3" (720mm) Maximum Paper Media width Up to 23.6" (600mm)/s cutting speed Up to 400g cutting force

Applications:

Suitable for stickers, POP signs and graphics, shop signs, window signs logos, and graphics. For indoor or outdoor use on windows, doors, walls, signboards, cars, motorcycles, even on clothing: hats, and other fabrics.

Product Highlights:

?Streamlined design, with a luxurious and modern appearance.
?Steel sting roller made with Japanese technology which guarantees motion precision.
?Single-key operation that regulates force and speed independently.
?Large screen LCD and function keys settled, and USB interface.
?Our factory owns the R&D right of this cutting plotter.
?Compatible software: Flexisign, CorelDraw, and Artcut.
?Standard HPGL language format, more compatibility and direct communication with CORELDRAW.

Spare Parts:

Roland blade (30, 45, and 60 degrees): + \$1.5 (common blade) / \$3 (A-grade blade)

Brief Introduce of Cutting Plotter:

?The cutting plotter is a common device in the advertising industry. You can transfer data to the plotter from `the` computer or by using a USB device (offline working). USB Device on Cutting Plotter is one of the new technologies promoted by our company. Benefited by such function, people can use a USB FLASH STORAGE instead of a computer to input and output files into `the` plotter. Using this, can solve all breakdowns caused by the connection between computer and cutting plotter.

?Process: the user should make a design, using compatible software; to set the type and size of the letter, and graphics needed. After the design is finished and cutting content is set, the user can send the file to the plotter. The computer controls the plotter and drives the

engraver to cut the letter and graphics (normally the vinyl and plastic film).

Details

Interface	COM, USB
Control Panel	Over-head, with LCD
Cutter Press	10-500g
Cutting Precision	0.1" (3mm)
Max. Cutting Thickness	0.5mm
Max. Cutting Speed	0.8"-23.6" (20-600mm)/s
Max. Cutting Width	24.4" (620mm)
Max. Paper Feed Width	28.3" (720mm)

Specifications

Paper Feeding Mode Controller Control Panel Driver Maximum Paper Feeding Width	M-shaped bracket 16 bit CPU Over-head, with LCD High-speed step motor, micro-step driver 28.3" (720mm)
Maximum Cutting Width	24.4" (620mm)
Cutting Speed	0.8"-23.6" (20-600mm)/s
Maximum Cutting Length	Limitless
Maximum Cutting Thickness	0.5mm
Knife Press	10-500g(digital adjustment)
Minimum Size for Cutting Letters	0.1" (3mm)
Repetition Precision	±0.1mm
CPU	Double CPU
Type of Tool	Carbide blade
Type of Plot Pen	All types of plot pens with a 0.47" (12mm) diameter
Plotting Instructions	DMPL
Interface	COM, USB
RAM	128K-2M
Real cutter softball	?
Emergency stop	?
Power Supply	AC90V-AC240V 50Hz-60Hz 60W
Power Consumption	50W
Machine Dimensions	36.2"x10.2"x9.8" (920x260x250mm) (stand not included)
Machine Weight	28.7lb (13kg)
Packaging	Carton box
Packing Size	39.8"x14.2"x14.2" (1010x360x360mm) (stand not included)
Gross Weight	37.5lb (17kg)

Tags

24" desktop



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com