



3-SMD 3528 Non water-proof module 74x12mm

Item Code: LED module-LBY-3F12T7412-3CNWF



FOB Price: **\$0.33/pc**

Mini Order: 200 pcs

Average Rating: 1b (kg)

[Inquire Now](#)


Overview

Characteristics:

- . High brightness LED SMD as a lamp-house, with wide angle view and a small aperture.
- . Controlled by the chips with constant current, has a steady current between the cathode and the anode.
- . Low voltage, safe and jarless.
- . With a settled orifice and 3M gummed paper, very convenient to install.
- . Longlife above 80,000hrs.
- . Low power consumption, energy conservation and made for save electricity.

Usage:

LED SMD modules are widely used for solid lighting character, LED signs, LED lighting box, scenery designs and decoration, etc.

Sample:

Specifications

Basic parameter			
Color	Red yellow blue green white	LED type	3528 SMD
LED quantity	3PCS	Demension	2.9"*0.5"*0.2" (74*12*6mm)
Module interface	Gray0.5mm 0.1"*3.0" (2*75mm) RVleads	Interface definition	Gray anode,white cathode
Cluster quantity	20pcs	Module space between	
Weight	0.4oz (10g)±5%	Lifespan	MTBF>50000hours
Enviroment parameter			
Working temperature	-40°C?60°C		
Outdoor level	IP20 not waterproof		
Electronic specification			
Input voltage	D12V±5%	Max power	0.21 W
Driving mode	Invariablenes Voltage! (Insure every LED working under the invariablenes voltage)		
Lighting capability			

Luminous flux 0.6floz (18lm)

Beam angle 120°



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com