



3-SMD 5050 RGB Water Proof Module 80x14 mm

Item Code: LED module-LBY-5F12T8014-3RGBWF



FOB Price: **\$0.98/pc**

Mini Order: 200 pcs

Average Rating: 1b (kg)

[Inquire Now](#)

Overview


Characteristics:

- . High brightness LED SMD as a lamp-house, having a wide angle view and petty aperture.
- . Controlled by the chips with constant current, having constant working current and indiscriminate between the cathode and anode.
- . Low voltage, safe and jar less.
- . With a settled orifice and 3M gummed paper, very convenient to install.
- . Long life time, above 80000hrs.
- . Low power consumption, energy conservation and saving electricity.

Application:

This LED SMD module is used for solid lighting character, LED signs, LED lighting box, scenery designs, décor, etc.

Sample:



Details

LED Number	3
SMD Package Model	5050
Color	RGB
Shape	Rectangular
Brightness	Medium
Material	Plastic

Specifications

Basic parameters			
Color	Red, yellow, blue, green, white	LED type	5050 SMD
LED Qty	3PCS	Dimension	3.1" x 0.6" x 0.2" (80 x 14 x 6mm)
Module interface	Yellow/Red/Green/Blue 0.2" x 0.02" (4 x 0.5mm) 0.1" x 2.4" (2 x 60mm)RVleads	Interface definition	Yellow anode, Red/Green/Blue cathode
Cluster Qty	20pcs	Module space between	2.4" (60mm)±5%
Weight	0.5oz (15g)±5%	Lifespan	MTBF>50000hours
Environment parameters			

Working temperature	-40℃?60℃		
Defend grade	IP65 competely satisfies the outdoorlighting standard		
Electronic specifications			
Working input voltage	D12V±5%	Max power	0.63 W
Driving mode	Invariable Voltage! (Insure every LED working under the invariable voltage)		
Lighting capability			
Luminous flux	1.9floz (54lm)		
Beam angle	>110°		



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com