

3-SMD 5050 Water proof module 74x12mm

Item Code: LED module-LBY-5F12T7412-3CWF



FOB Price: **\$0.98/pc**

Mini Order: 200 pcs

Average Rating: Ib (kg)

Inquire Now

Overview

Characteristic:

- . High brightness LED SMD as a lamp-house, having a wide angle view and petty aperture.
- . Controlled by the chips with constant current, having constant working current and indiscriminate between the cathode and anode.
- . Low voltage, safe and jar less.
- . With a settled orifice and 3M gummed paper, very convenient to install.
- . Long life time, above 80000hrs.
- . Low power consumption, energy conservation and saving electricity.

Application:

This LED SMD module is used for solid lighting character, LED signs, LED lighting box, scenery designs, décor, etc.

Sample:



Sample 1 Sample 2

Details

LED Number	3		
SMD Package Model	5050		
Color	White		
Shape	Rectangular		
Brightness	Medium		
Material	Plastic		

Specifications

Basic parameters				
Color	Red, yellow, blue, green, white	LED type	5050 SMD	
LED Qty	3PCS	Dimension	2.9" x 0.5" x 0.2" (74 x 12 x 6mm)	
Module interface	Gray 0.5mm 0.1" x 3.0" (2 x 75mm) RVleads	Interface definition	Gray anode, white cathode	
Cluster Qty	20pcs	Module space between		
Weight	0.4oz (10g)±5%	Lifespan	MTBF>50000hours	
Environment parameters				
Working temperature	-40°C?60°C			
Defend grade	IP65 competely satisfies the outdoorlighting standard			
Electronic specifications				
Working input voltage	D12V±5%	Max power	0.63 W	
Driving mode	Invariable voltage! (Insure every LED working under the invariable voltage)			
Lighting capability				
Luminous flux	1.9floz (54lm)			
Beam angle	120°			























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com