

3 SMD LED Module, White 5050 LED(38mmx38mm stainless steel)

Item Code: LED module-LBY-TH383F-CWF



FOB Price: **\$2.09/pc**

Mini Order: 200 pcs

Average Rating: Ib (kg)

Inquire Now


Overview

Characteristic:

- Using high brightness LED SMD as the lamp-house, having wide viewing angle and petty aperture.
- Controlled by the chips with constant current, having constant working current and indiscriminate between the cathode and anode.
- Low voltage, safe and jar less.
- With a settled orifice and 3M gummed paper, very convenient to install.
- Long life time. above50000hrs.
- Low power consumption, energy conservation and saving electricity.

Application:

This LED SMD module is widely used for solid lighting character, LED signs, LED lighting box, scenery designs, décor, etc.



Details

LED Number	3
SMD Package Model	5050
Color	White
Shape	Square
Brightness	High
Material	Metal

Specifications

Basic parameters

Color	White, red, yellow, blue, green	LED type	5050 SMD	
LED Qty	3 pcs	Dimension	38 x 38 x 4mm	
Module interface	Gray 0.5mm2×75mm RVleads	Interface definition	Gray anode, white cathode	
Cluster Qty	20pcs	Module space between		
Weight	25g±5%	Lifespan	MTBF?50000hours	
Environment parameters				
Working temperature	-30?~ 50?			
Defend grade	IP65			
Electronic specifications				
Working input voltage	D12V±5%	Max power	0.6W	
Driving mode	Invariable Voltage! (Insure every LED working under the invariable voltage)			
Lighting capability				
Luminous flux	48lm			
Beam angle	>120°			



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com