


40.1" (1.02m) Coated Backlit

Item Code: BS-CB005-40R-GL-1



FOB Price: \$116/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Samples:





sample 1 sample 2

Specifications

Metric **Test Method** Item

Weight 510±10gsm DIN53352 BS3424 **Breaking Strength** 2100/1850N/2.0" (5cm) DIN53354 BS3424 **Tearing Strength** 300/250N DIN53356 BS3424 Adhesion 80N/2.0" (5cm) DIN53357 BS3424

Width Up to 11.5' (350cm) (1010)

FR Certification We can reach:M2,B1,B2,DIN75200,NFPA701

Lacquering Products can be lacquered with ACRYLIC or PVDF

Cd We can reach: EN71-3

























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com