

40.1" (1.02m) Coated Frontlit

Item Code: BS-CF013-40R-GL



FOB Price: **\$99.51/roll**

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.



Specifications

Weight

Item Metric

440±10

N/2.0" (5cm) **Breaking Strength** 1800/1300 DIN53354 BS3424 **Tearing Strength** 180/165 DIN53356 BS3424 Ν DIN53357 BS3424 Adhesion 80 N/2.0" (5cm)

gsm

Width Up to 11.5' (350cm) (0505)

We can reach:M2,B1,B2,DIN75200,NFPA701 FR Certification

Lacquering Products can be lacquered with ACRYLIC or PVDF

We can reach:EN71-3 Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%

















DIN53352 BS3424







Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com