



1600mm(63") Master Mounting Cold Laminator

Item Code: FMJ-1600-II plus



FOB Price: **\$1,326/set**

Mini Order: 1 set

Shipping Weight: ★★★★★

Average Rating: 554.4lb (252kg)

[Inquire Now](#)

Overview

FMJ-1600-II plus: MASTER MOUNTING COLD Laminator

FMJ-II plus series cold laminator is based on the theory of FMJ-CIIZ series, master mounting cold laminating

Equipped with foot-pedal switch, no need to heat.

A perfect fit for entry level customer, who looking for an affordable and professional cold laminator for their projects

This new model can be widely used for pre-masking vinyl graphic, mount prints on substrate, over laminating inkjet prints and so on.

Product Highlights:

- . Maximum working film width 55", 63" for your option.
- . The cold laminator has simple structure, reasonable, humane and low cost characteristics.
- . Since it was produced; it has been popular at the roller for supporting film, guiding roller and roller for collecting back-paper.
- . 5" bigger rollers for best quality laminating control. Maximum nip opening up to 1" for a wide material range of film and substrate.
- . The cold laminator saves manpower and is easy to operate. As a result of the novel structure it has been a good market since it is appeared.
- . FMJ-1600-II plus is based on the theory of FMJ-1600-CIIZ, because we have been the profound understanding principle of laminator so a simple new laminator which is auto stripping and collecting back paper is developed.
- . The cold laminator is operated conveniently and high efficient-It can be continued laminating or the longer picture laminated and realizing the automatic stripping film and collecting back-paper which rely on the rotary force of the upper and lower roller.

Application:

After printing equipment. Available for photograph productions, advertising, shops, copy shop, lamination work, protective layers on books covers and color pages, documents, charts, drawings, indoor advertising and products.

Applicable Laminating Medium:

Photopaper, PP, self-adhesive PP, backlit film or transparent film.

Warranty and after sales services:

One year of warranty except the spare parts.

24 hours technical support by mail or phone.

User friendly English manual on how to use the machine and accomplish the maintenance.

Details

Maximum Laminating Width	63" (1600mm)
Maximum Laminating Thickness	1" (25mm)
Rollers Diameter	5" (128mm)
Maximum Laminating Speed	197" (5m) / min
Maximum Internal Diameter of	3"
Profile	Semi-auto cold laminating machine (Automatic take-

up rolls of back paper), with functions of single sided

Specifications

cold laminating and mounting by electric. It can be

operated by hand or electric. Upgraded and Hot sales

Specification Form	
Max. Laminating Thickness	0.9" (23mm) transmittance, free of bubbles and snowflake point! It
Laminating Speed	0-197" (5m) / min saves manpower and is easy to operate.
Forward / Reverse	Yes
Foot Pedal	Yes
Roller's Diameter	5.1" (130mm)
Roller Pressure	Manual
Max film length	3937.0" (100m)
Emergency Stops	Yes
Auto Rewind Liner Pickup	Yes
Media Core Size	3"
Power Supply	AC 80V-110V, AC 110V-240V, 50Hz or 60Hz



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com