



## 6M Upgrade Continuous HF Welder for Banner & Tarpaulin

Item Code: CS-3000S



FOB Price: **\$15,630/pc**

Mini Order: 1 pc

Shipping Weight: ★★★★★

Average Rating: 1562.0lb (710kg)

[Inquire Now](#)

### Overview

The Continuous HF Welder is a set of brand new HF welding equipment (a newly designed equipment), based on a unique continuous HF welding theory. New improved 3000T machine and occupying less space, 30% room saving. These improvements extend the application to mid-weight fabric PVC materials, such as tents, pool liners, mobile liquid tank, and so on.



Features:

Patented idea Combination of HF and continuous movements, applying continuous moving welding head to HF welding process, we show you a new idea of HF welding.

#### Optional table length

Modular welding table length is available from `6m` (236.2") up to 30m (1181.1"), in every 3.

#### Smooth and perfect output

Consistent and even HF power together with pressure affected in the materials through the whole welding process, lead to a smooth and perfect joint.

#### High speed

Maximum welding speed is 4 meters (157.5") per minute, for time-saving, which greatly improves the efficiency in production.

#### Low power request

Maximum power request is 3 kilo watt, which equals to a tenth part of other HF welder.

Standard configuration for welding table is 6m; table module length is 3m (118.1").

---

## Specifications

---

| Specification Form          |  |
|-----------------------------|--|
| Table length:               | Free Choice (118.1" (3000mm)/ piece, Standard: 236.2" (6000mm))  |
| Floor Requirement:          | 5.7 m2   |
| Packing Size: Main Machine: | 39.4"*39.0"*65.4" (1000*990*1660mm)                              |
| Welding table:              | 123.6"*35.0"*23.6" (3140*890*600mm)                              |
| Working table length:       | 236.2" (6m) (standard) (longer table length is available: 6m+3n) |
| Welding Width:              | 0.4"-1.6" (10mm-40mm)  |
| Weight:                     | 1565.3lb (710kg)   |
| Welding Speed:              | 39.4"-236.2" (1-6m)/min  |
| Rated Voltage:              | Single Phase 50Hz, 220V±10%                                      |
| Rated Power:                | 3KW  |
| Frequency:                  | 27.12MHz ±0.5%   |
| Working Pressure:           | 4.4-8.8lb (2-4Kg)  |
| Cooling:                    | Air cooling  |
| Air Requirement:            | 6 bar  |

---



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com