

86.6" (2.2m) Laminated Frontlit

Item Code: BS-LF009-86R-GL-W/G



FOB Price: \$107/roll

Mini Order: 40 rolls


Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.



. Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Specifications

Item		Metric	Test Method
Neight	440±10	gsm	DIN53352 BS3424
Breaking Strength	635/451	N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	125/107	Ν	DIN53356 BS3424
Adhesion	60	N/2.0" (5cm)	DIN53357 BS3424
Nidth	Up to 11.5' (350cm) (0305)		
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701		
Lacquering	Products can be lacquered with ACRYLIC or PVDF		
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3		



 $\label{eq:copyright} @ 1999-2012 \ by \ Beijing \ ChinaSigns \ Information \ Company \ Limited \ All \ Rights \ Reserved.$

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com