


98.4" (2.5m) Laninated Backlit

Item Code: BS-LB002-98R-GL



FOB Price: \$165/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, Digital printing, Screen printing for Banner and outdoor, indoor digital printing for media inkjet.





Details

Width	98.4" (2.5m)
Length	54.6Y(50m)
Speci-	300*500 18*12

Specifications

Item Metric **Test Method**

Weight	610±10	gsm	DIN53352 BS3424	
Breaking Strength	635/451	N/2.0" (5cm)	DIN53354 BS3424	
Tearing Strength	125/107	N	DIN53356 BS3424	
Adhesion	60	N/2.0" (5cm)	DIN53357 BS3424	
Width	Up to 11.5' (350cm) (0305)			

FR Certification We can reach:M2,B1,B2,DIN75200,NFPA701

Products can be lacquered with ACRYLIC or PVDF Lacquering

Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se% We can reach:EN71-3























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.