

98.4" (2.5m) Laninated Frontlit

Item Code: BS-LF006-98R-1-GL-G



FOB Price: \$82.98/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.



Details

Width	98.4" (2.5m)
Length	54.6Y(50m)
Speci-	200*300 18*12

Specifications

Item	Metric	Test Method	
Weight	300±10 gsm	DIN53352 BS3424	
Breaking Strength	497/301 N/2.0" (5cm)	DIN53354 BS3424	
Tearing Strength	85/65 N	DIN53356 BS3424	
Adhesion	60 N/2.0" (5cm)	DIN53357 BS3424	
Width	Up to 11.5' (350cm) (0203)		
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701		
Lacquering	Products can be lacquered with ACRYLIC	or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3		





















Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.