


98.4" (2.5m) Laminated Backlit

Item Code: BS-LB003-98R-GL



FOB Price: \$183/roll

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . 32% above high light-admitting quality.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, Digital printing, Screen printing for Banner and outdoor, indoor digital printing and so on.



Specifications

Test Method Item Metric

Weight DIN53352 BS3424 630±10 gsm **Breaking Strength** N/2.0" (5cm) DIN53354 BS3424 950/875 **Tearing Strength** 135/122 Ν DIN53356 BS3424 Adhesion 60 N/2.0" (5cm) DIN53357 BS3424

Width Up to 11.5' (350cm) (0305)

FR Certification We can reach: M2, B1, B2, DIN75200, NFPA701

Lacquering Products can be lacquered with ACRYLIC or PVDF

Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se% We can reach:EN71-3





















Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com