

Coated Mesh Fabric

Item Code: BS-M112-TC



FOB Price: \$1.64/sq.m

Mini Order: 40 rolls

Average Rating: Ib (kg)

Inquire Now

Overview

Product Characteristic:

- . High strength, anti-tensile, anti-tearing.
- . Good ventilating ability, natural lighting.
- . Color expressive.
- . Three-dimensional printing effect available.
- . Anti-typhoon, thus could be put on the roof of the building.
- . Flame retardant, safe.
- . weather resistant, suitable for both indoor and outdoor.
- . Low cost and easy to use.

Product Description:

Smooth, high bonding strength, goog and stable ink absorbing, self-cleaning, fast drying up, perfect pringting effect, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Digital printing, Screen printing for Wall murals, Building cover & signboard.

Details

 Width
 3.4-10.5 ft(1.02-3.20m)

 Length
 164.0 ft(50m)

Thickness(g/sq.m)

270?m

Specifications

Item	Metric	Test Method
Weight	270 gsm	DIN53352 BS3424
Breaking Strength	850/1000 N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	190/200 N	DIN53356 BS3424
Adhesion	/ N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (0510)	
FR Certification	M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC c	or PVDF
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3	



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com