



High Power LED Module, White Osram LED 1w (52mmx36mm)

Item Code: LED module-FT-ZS01-1WF



FOB Price: **\$2.06/pc**

Mini Order: 200 pcs

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Characteristics:

- High Luminous Efficacy .The illuminant is made up of Osram brand,lighting effect is very high, the color temperature is consistent.
- All injection molding, water proof, IP 65.
- Lighting angle is 120°, well-distributed.
- Two holes on both ends for installation, 3M doubleside glue in back, easily installed.
- Widely used in big characters?poster card?sign?architecture, etc.
- Caution: Less than 20pcs modules in series connection, can't be used directly outdoor.
- High quality reliable.

Application:

This led moduel widely used in thickness 18-30cm lighting letters, adverting light box, sign board, etc. For this led moduel, the best application depth are 20-25cm.

Details

| | |
|-------------------|-------|
| LED Number | 4 |
| SMD Package Model | 5050 |
| Color | White |
| Shape | Other |
| Brightness | High |

Material

Plastic

Specifications

| Basic parameters | | | |
|---------------------------|---|----------------------|---------------------------|
| Color | White | LED type | 5050 SMD |
| LED Qty | 4 pcs | Dimension | 34 x 34 x 4mm |
| Module interface | Gray 0.5mm2×75mm RVleads | Interface definition | Gray anode, white cathode |
| Cluster Qty | 20pcs | Module space between | |
| Weight | 14g±5% | Lifespan | MTBF?50000hours |
| Environment parameters | | | |
| Working temperature | -30?~ 50? | | |
| Defend grade | IP65 | | |
| Electronic specifications | | | |
| Working input voltage | D12V±5% | Max power | 0.7W |
| Driving mode | Invariable voltage! (Insure every LED working under the invariable voltage) | | |
| Lighting capability | | | |
| Luminous flux | 60lm | | |
| Beam angle | 120° | | |



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com