




Laminated Frontlit Flex Banner

Item Code: BS-LF007-1-GL-G



FOB Price: **\$0.65/sq.m**

Mini Order: 40 rolls


Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.



Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-

UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Signage, Digital printing, Screen printing for Banner and outdoor, indoor digital printing and so on.

Details

Speci-	200*300 18*12
Width	3.3-10.5 ft(1-3.2m)
Length	164.0 ft(50m)
Thickness	320

Specifications

Item	Metric	Test Method
Weight	340±10 gsm	DIN53352 BS3424
Breaking Strength	497/301 N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	85/65 N	DIN53356 BS3424
Adhesion	60 N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (0203)	
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3	



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com