




One Way Vision (3 years Warranty)

Item Code: BS-PO2000-PY



FOB Price: **\$3.27/sq.m**

Mini Order: 50 rolls

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Description:

. **Surface film:** Best 180 micron Black/White laminated film, with the good whiteness, wonderful hiding performance, scalability-resistant, anti-UV, good ink absorbing, bright and colorful printing screen.

. **Bottom paper:** 140gsm wooden-pulp paper.

. **Glue:** Use the high-quality and imported glue so that the products can truly achieve non-residual gum, none-spilling gum, removable and none-residual.

. **Black coating technique:** The coating has the excellent adhesion of the PVC film, good intimacy of the acrylic type glue, as well as the excellent performance of climate-resistant. From `both` technology and process, it achieve the perfect consistency on PVC film and black coating, black coating and acrylic type glue, as well as the acrylic type glue and the object which is pasted. It finds fundamental solution of residing the black glue as other coating one way vision, as well as the problem of dirty surface and unclear picture which is made by the spilling glue from `the` hole of other one way vision.

. This is a reflective one way vision material, so we still can see the picture during the night as long as the material can meet light from `its` surroundings.



The application of the printer type:

Solvent: Vutek, Noel, Scitex, DGI, Teckwin, Yaselan, Flora, Fitto, Infinity, GongZheng, LiYu.

ECO solvent: Mutoh, Roland, 118.1" (3m), Mimaki and others.

The scope of application:

Used for the wide format digital printing indoor and outdoor, the ECO solvent printing and screen printing, this kind of one way vision film is widely applied in the advertising of the windows of the buses, taxis, subway and other means of transport, glass wall, windows of shopping mall etc.

Note:

. All the products take the lead in the use of environmental-friendly PVC membrane in the industry and can access to U.S. and European markets directly. We are able to provide the CE (products safety certification of European Community) and RoHS (certification of environmental protection products) for you if necessary.

. If you need the better performance of the ink absorbing, we do have the products using the complex bottom paper.

Details

Width	38.6",42",50"(1.0m,1.1m,1.3m)
Length	164.0 ft,328.1 ft(50m,100m)
Glue	Removable,Transparent
Line	140
PVC Face	180 Micron
GSM	140

Specifications

Reflective one way vision-FUF2618								
mode	PVC surface material		glue color	bottom paper		products disciplines		roll diameter (MM)
	PVC film thickness (micron)	products thickness (micron)		paper layer	weight	length(M)	width(M)	
FUF2618	260±5	285±5	transparent	coated paper	180	164.0' (50m) 328.1' (100m)	38.6" (0.98m) 50.0" (1.27m) 53.9" (1.37m) 59.8" (1.52m)	0.1" (1.45mm) 0.1" (1.60mm)



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com