

P16 Outdoor Tri-Color LED message board

Item Code: TCMB-LJ-P16Outdoor



FOB Price: \$982/sq.m

Mini Order: 1 roll

Average Rating: Ib (kg)

Inquire Now

Overview

The Tri-Color LED Screen is widely used for indoor and outdoor display messaging, outdoor AD sign display and much more. Features a wide range angle and distance view, uniform illumination and excellent brightness. There is a low rate of failures; the LED screen has a long lifespan, low consumption of energy and excellent performance. Application:

This Tri-Color LED Screen is designed for outdoor information display, and outdoor AD sign display etc.

Application:

This Single Color LED Screen is designed for outdoor information, AD sign display and other outdoor uses.

Specifications

Specification:

Pixel pitch	0.6" (16mm)
Pixel configuration	2R 1G
Pixel Density	3906dots/?

Ideal viewing distance	29.5'-85.3' (9m-26m)
Ideal viewing angle	160°
Control method	Synchronization/ Asynchronization
Driving method	Constant 1/4 scanning
Frame frequency	?60HZ
Refresh frequency	?180HZ
Max. power	<300W
Brightness	?5000cd/?
IP grade	IP65 front, IP54 back
Voltage range	AC220v/110±10%
Ideal temperature	_10??+45?
MTBF	More than 10,000 hours
Lifespan	10,000 hours























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com