P4 Indoor integrated 3 in 1 Full Color Screen

Item Code: FC-LJ-P4integrated

FOB Price: **$9,574/sq.m**

Mini Order: 1 roll

Average Rating: lb (kg)

[Inquire Now]

Overview

Description:
3 in 1 Integrated full color is a patented product. It has color blending ability, high brightness and a wide viewing angle.

Advantages:
. Highest resolution: up to 62500dots/sq.m which makes good exhibition effects and vivid images in small areas (2sqm/3sqm).
. Color blending: With RGB in one pixel plus reasonable reflect cavity and permutation of RGB in pixel, the color has been mixed as lighting.
. LED lamp will get the blending effect at some distance.
. Anti-static properties: Innovative mechanical design of cavity reflection and configuration of the RGB chips.
. High reliability: LED DOT-MATRIX has great brightness.
. Wide viewing angle: 140° (horizontal)
. Color consistency: Highly bright colors and 100% peroxide resin of the LED chips make the perfect display effect.
. High brightness: The 4 x 4 module (utility model patent), can achieve a 1/4 scanning rate and ia able to further enhance the brightness.

Details:

Name:Lnk-ID4-RGB-16I
Size: 512mm×384mm×120mm

Size: 256mm×128mm
Resolution: 64×32

Pixel pitch: 4mm
Size of pixel: 3mm (circle)

Details

Environment	Indoor

Specifications

Specifications:

Pixel pitch	0.2" (4mm)	Pixel size	
Block module size	1.3"*1.3" (32*32mm)	Pixels in block module	
Module size	10.1"*5.0" (256*128mm)	Module resolution	
Cabinet size	20.2"*20.2"*4.7"(512*512*120mm)	Cabinet resolution	
Cabinet area	0.0315 m²	Pixel density	
Pixel configuration	1R1PG1B	Best viewing distance	
Brightness	?1800cd/ m²	Maximum power consumption	
Horizontal viewing angle	140°	IP grade	
Driving device	constant current	Driving method	
Colors	16777216	Color temperature	

Gray scale	14 bits	Refresh frequency	
Control method	Synchronization	Working temperature	
Frame frequency	?60Hz	MTBF	
Working voltage	AC220V/110V±10%	Life span	