

P4 indoor singlecolor LED messageboard

Item Code: SCMB-LJ-P4indoor



FOB Price: \$1,244/sq.m

Mini Order: 1 roll

Average Rating: Ib (kg)

Inquire Now

Overview



The Double Color LED Screen is widely used for indoor display messaging. It is featured

with a wide range angle and distance view, uniform illumination and excellent brightness. There is a low rate of failures; the LED screen has a long lifespan, low consumption of energy and excellent performance.

Application:

The Single Color LED Screen is design to function as an indoor scrolling message display; it can also work in a network system with other displays. It can be used in banks, hospitals, mall, hotels and much more.

Specifications

Specification:

Pixel pitch

0.2" (4mm)

Pixel configuration	1R
Pixel Density	62500dots /?
Ideal viewing distance	29.5'-85.3' (9m-26m)
Ideal viewing angle	120°
Control method	Synchronous
Driving method	Constant 1/16 scanning
Frame frequency	?60HZ
Refresh frequency	?180HZ
Max. power	<300W
Brightness	?200cd/?
Voltage range	AC220v/110±10%
Ideal temperature	-10??+45?
МТВГ	More than 10,000 hours
Lifespan	10,000 hours



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com