

P7.62 semi outdoor single color LED messageboard

Item Code: SCMB-LJ-P7.62 semioutdoor



FOB Price: \$753/sq.m

Mini Order: 1 roll

Average Rating: Ib (kg)

Inquire Now

Overview

This Single Color LED Screen is widely used for the semi outdoor message display. It featured with its big range viewing angle and distance, high paleness, luminance uniformity, excellent brightness, low failure rate, long service life, low consumption of energy and high cost performance.

Application:

This Single Color LED Screen is best designed for the semi outdoor display solutions as store LED scrolling message display, and also can be networked together with others for message display in banks or conferences.

Specifications

Specification:

Pixel pitch	0.3" (7.62mm)
Pixel configuration	1R
Density of pixel	17222dotS/?
Best viewing distance	29.5'-85.3' (9m-26m)
Best viewing angle	140°

Control method	Synchronization/ Asynchronization
Driving method	Constant 1/8 scanning
Frame frequency	?60HZ
Refresh frequency	?180HZ
Maximize power	<300W
Brightness	>300cd/?
IP grade	IP20 front
Working voltage	AC220v/110±10%
Working temperature	– 10? + 45?
MTBF	More than 10,000 hours
Life span	10,000 hours























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com