

Output	DC Voltage	12V	24V
	Constant current operation voltage rated	8-12V	14-24V
	Rated current	5000ma	2.5ma
	Rated power	60W	60W
	Ripple&noise(max.)	200mV (p-p)	300mV (p-p)
	Voltage tolerance	±5.0%	±5.0%
	line regulation	±1.0%	±1.0%
	Load regulation	±2.0%	±2.0%
	Setup time	2500mS. 80mS 230VAC/115VAC	
Input	Voltage range	90-277VAC	
	Frequency range	47-63Hz	
	Efficiency	85%	86%
	AC current	1.4A/115VAC 0.7A/230VAC	
	Inrush current	20A/23VAC	
Protection	Over current	95-108%	
		Protected mode: constant current limiting, load exception condition is	
	Short circuit	Hiccup mode: abnormal condition is removed, can automatically resume the	
Environment	Over Voltage	Protected mode: turns off the output voltage, after the restart recovery	
	Working Temp	-20—60°	
	Working humidity	20—95%RH	
	Storage TEMP humidity	-40~+80° , 10~95%RH	
	TEMP coefficient	±0.03%/° C (0—50° C)	
Safely& EMC	Vibration	10-500Hz, 5G 12min/round, X,Y,Z 72min	
	Safety standards	GB4943	
	Withstand voltage	I/P-O/P; 3KVAC	
	Isolation resistance	I/P-O/P;100M Ohms/500VDC/25° C/70%RH	
Other	EMC standards	EN61000-4-2, 3, 4, 5, 6, 8, 11; ENV50204. EN61547, EN550	
	MTBF	≥40Khrs, MIL-HDBK-217F (25° C)	
	Dimension	130*62*31 (L*W*H)	
	Weight	430g	