

# **Product Specification**

## Model NO: LEDM-GKL-MFW8A1D

Name: AC100V Injection Module-Terminator-2

Version: 1st Edition 2016



Customer Confirmed	Checked	Approved	Editor



## **Description:**

- 1, Adopt high quality LED as light source, high brightness, uniform lighting, good Anti-static;
- 2, AC100V-110V/60Hz input; P.F>0.9;
- 3, Nice design with 155 °optical lens;
- 4, Circuit design with constant current, over-temperature and short circuit protection function;
- 5, Use fire-resistant material, fireproof up to U94V-0 and waterproof up to IP67;
- 6, No need power supply; no wiring loss; no voltage-dropping; single cuttable; easy installation;
- 7, Certificate: UL, CE, Rosh, LM80, IP67

#### Application: Advertising sign with 10-35mm and lighting box etc.

Voltage:	AC100V-110V/60Hz	Color;	Rice white
Power:	2.3W	Material:	PVC
Lumens:	212 lm	Weight(50PCS):	3250g
Beam angle:	155 °	Connection Qty:	100PCS/string
PF:	>0.9	Fixing Screw:	M3 screw
LED Qty:	3PCS	Таре:	3M backing tape
CCT:	White	Working Temp.:	-20~55°C
Luminous efficacy:	92 lm/w	Storage Temp.:	-40~80°C
IP rate:	IP67	Warranty:	5year
Dimensions	110*28*8.5mm		

## **Parameters of light source:**

LED	SMD LED (LM80)
Life spam	>30000H
Ra	≥80



The final interpretation of the product made by GK lighting all subject to change without notice.

# Lighting distribution:





lighting distribution

lighting spot

## **Dimension:**(Unit: MM):





Installation and cable connecting diagram:





\*Note: For more information, please refer to user manual and installation manual at installations