

Product Specification

Model NO: LEDM-GKL-MFW8A1D

Name: AC220V Injection Module-Terminator-2

Version: 1st Edition 2016



Customer Confirmed	Checked	Approved	Editor



Description:

- 1, Adopt high quality LED as light source, high brightness, uniform lighting, good Anti-static;
- 2, AC 220-AC240V 50Hz/60Hz input; P.F>0.9;
- 3, Nice design with 155° optical lens;
- 4, Circuit design with constant current, over-temperature and short circuit protection function;
- 5, Use fire-resistant material, fireproof up to U94V-0 and waterproof up to IP67;
- 6, No need power supply; no wiring loss; no voltage-dropping; single cuttable; easy installation;
- 7, Certificate: UL, CE, Rosh, LM80, IP67

Application: Advertising sign with 10-35mm and lighting box etc.

Parameters of product:

Voltage:	AC220V-AC240V 50Hz/60Hz	Color	Rice white
Power:	2.5W	Material:	PVC
Lumens:	220lm	Weight(50PCS):	3250g
Beam angle:	155°	Connection Qty:	100PCS/string
PF:	>0.9	Fixing Screw:	M3 screw
LED Qty:	3PCS	Tape:	3M backing tape
ССТ:	White	Working Temp.:	- 20~55 ℃
Luminous efficacy:	86lm/w	Storage Temp.:	- 40~80 ℃
IP rate:	IP67	Warranty:	5year
Dimensions	110*28*8.5mm		

Parameters of light source:

LED	SMD LED (LM80)
Life spam	>30000H
Ra	≥80
ССТ	6500-7000K/8000-10000K



 8.5 ± 0

The final interpretation of the product made by GK lighting all subject to change without notice.

Lighting distribution:





Installation and cable connecting diagram:



*Note: For more information, please refer to user manual and installation manual at installations